



Ordering Information (Standard / Industrial Grade RoHS II)

Bauform	Dielectric	Wert	Toleranz	Spannung	Kappen	Chipdicke	Gurt
1812	RN	223	K	500	N	(X)	T(M)
0402 0504 0603 0805 1206 1210 1515 1808 1812 1825 2020 2220 2225	< 250V RN=C0G RoHS II RB=X7R RoHS II W=X5R RoHS II RM=C0G RoHS II nonmag RC=X7R RoHS II nonmag BB=X7R BMERoHS BW=X5R BMERoHS	472 (4.7nF) 102 (1nF) 103 (10nF) 104 (100nF) 105 (1µF) 106 (10µF) 107 (100µF)	B=0,1p C=0,25 D=0.5p F= 1% G= 2% J= 5% K=10% M=20%	4R0 = 4V 6R3= 6.3V 100 = 10V 160 = 16V 250 = 25V 350 = 35V 500 = 50V 101= 100V 201= 200V	N Nickel Sperrschicht RoHS C Flexicap RoHS NG Gold Flash RoHS B CopperBar nonmagn RoHS	(X) Chip Dicke X080 X092 X100 X150	T Tape W Waffle Pack M Marking

Kappen: B = Copper Barrier for Sizes >0805