

+200°C HighTemp Class II maximale Kapazitätswerte



Volt	XX	0805	1206	1210	1515	1812	1825	2225	4540	6560	7565
25V	min max	120pF 0.082uF	120pF 0.220uF	1200pF 0.390F	150pF 0.820uF	150pF 0.680uF	470pF 1.5uF	470pF 1.8uF	1000pF 5.6uF	2200pF 15uF	2200pF 18uF
50V	min max	120pF 0.047uF	120pF 0.120uF	120pF 0.220uF	150pF 0.680uF	150pF 0.470uF	470pF 1.0uF	470pF 1.2uF	1000pF 4.7uF	2200pF 12uF	2200pF 15uF
100V	min max	120pF 0.018uF	120pF 0.047uF	120pF 0.100uF	150pF 0.270uF	150pF 0.150uF	470pF 0.470uF	470pF 0.470uF	1000pF 3.3uF	2200pF 8.2uF	2200pF 12uF
200V	min max	120pF 4700pF	120pF 0.022uF	120pF 0.047uF	150pF 0.150uF	150pF 0.100uF	470pF 0.150uF	470pF 0.220uF	1000pF 2.2uF	2200pF 4.7uF	2200pF 5.6uF
250V	min max	120pF 2700pF	120pF 0.010uF	120pF 0.027uF	150pF 0.082uF	150pF 0.047uF	470pF 0.120uF	470pF 0.150uF	1000pF 1.2uF	2200pF 2.7uF	2200pF 3.9uF
500V	min max	120pF 1000pF	120pF 2200pF	120pF 5600pF	150pF 0.018uF	150pF 0.010uF	470pF 0.027uF	470pF 0.033uF	1000pF 0.330uF	2200pF 0.680uF	2200pF 0.820uF
1000V	min max	120pF 150pF	120pF 390pF	120pF 820pF	150pF 2700pF	150pF 1500pF	470pF 4700pF	470pF 4700pF	1000pF 0.680uF	2200pF 0.150uF	2200pF 0.220uF
2000V	min max	----	----	120pF 150pF	150pF 560pF	150pF 220pF	470pF 1.2uF	470pF 1.5uF	1000pF 0.018uF	2200pF 0.039uF	2200pF 0.047uF
3000V	min max	----	----	----	----	----	----	----	1000pF 6800pF	2200pF 0.015uF	2200pF 0.018uF
4000V	min max	----	----	----	----	----	----	----	1000pF 2700pF	2200pF 5600pF	2200pF 8200pF

Verfügbare Kapazitätswerte gem. E-Reihe 1.0 1.2 1.5 1.8 2.2 2.7 3.3 3.9 4.7 5.6 6.8 8.2 (1.0, 10, 100, 1000, 10000 pF (10nF)
103 (10nF, 0.010uF), 104 (100nF, 0.100uF) andere Werte auf Anfrage

200°C E - Dielectric Class II Arbeitstemperaturbereich: -55°C bis +200°C

NOVACAP: 1206B104K500NT											
1206	B	104	K	500	N		T				
SIZE	DIELECTRIC	CAPACITANCE	TOLERANCE	VOLTAGE	TERMINATION	PACKAGING	MARKING				
0402	B = X7R+125°C	1st two digits are significant, third digit denotes number of zeros, R=decimal	B = ±0.10pF	160 = 16V	N=Nickel Barrier (100% Sn)						
0504	N = NPO+125°C		C = ±0.25pF	250 = 25V	P=Palladium Silver						
0603	S = X8R +150°C		D = ±0.50pF	500 = 50V	Y=Nickel Barrier (90%Sn/10%Pb)						
0805		1R0 = 1.0 pF	F = ±1%	101 = 100V							
1206	F = NPO+160°C	120 = 12 pF	G = ±2%	251 = 250V							
1210	G = HTX+160°C	471 = 470 pF	J = ±5%	501 = 500V							
1808	D = NPO+200°C	102 = 1,000 pF	K = ±10%	102 = 1000V							
1812	E = HTX+200°C	273 = .027 µF	M = ±20%	202 = 2000V							
1825	R = R2D+200°C	474 = 0.47 µF	Z = +80/-20%	302 = 3000V							
2221		105 = 1.0 µF	P = +100%/-0%	402 = 4000V							
2225				502 = 5000V							
4540				103 = 10000V							
6560											
7565											
		HTX = Class II									
		Dielectric									



Electronic Components and Logistics